



ELITE SERIES

GLUE DOWN FLOORING

PRO 12 COLLECTION



Stone Harbor
FC22100



Platinum 12
FC22200

FLOORING SPECS PRO 12

Plank dimensions:
7.24" x 48"
Wearlayer: 12 mil
Thickness: 2.0 mm
Carton: 60.36 SQ FT
Planks/box: 25

PRO 28 COLLECTION



Platinum 28
FC88100

FLOORING SPECS PRO 28

Plank dimensions:
9" x 48"
Wearlayer: 28 mil
Thickness: 4.5 mm
Carton: 24.81 SQ FT
Planks/box: 8

PRO 20 COLLECTION



Platinum 20
FC44100



Island
Sand
FC44200



Pearl
River
FC44300



Skylight
FC44400



Grey
Storm
FC44500



Pathway
FC44600



Shown here Pearl River

FLOORING SPECS PRO 20

Plank dimensions: 7.24" x 48"
Wearlayer: 20 mil
thickness: 2.5 mm
Carton: 48.29 SQ FT
Planks/ box: 20



PRICING
Call for Pricing

coordinating moldings (94" long) T-Moldings,
End Cap, & Reducer



ELITE SERIES

12 MIL 2.0MM GLUE DOWN VINYL WARRANTY

PRO 12 COLLECTION

15 YEAR RESIDENTIAL WARRANTY FOR DRYBACK FLOORING

Will not wear through.

Will be free of manufacturing defects.

Will not rip or tear from normal household use. (If Properly Protected)

Will not permanently indent from normal household use. (If properly Protected)

Will not discolor from the bottom-up from the underlayment panels, as well as mold, mildew or alkali.

Wear through is defined as loss of the floor design due to normal household use. We recommend using floor protectors. As a general rule of thumb, the heavier the item, the wider the floor protectors should be.

COMMERCIAL INSTALLATIONS 10 YEAR LIMITED WARRANTY

For commercial installations (example: common areas in multi-unit dwellings and low traffic retail shops) the product is warranted to be free from manufacturing defects for 10 years from the date of purchase. If a defect covered by this warranty is reported in writing to FORZACORE within 90 days of purchase, FORZACORE will supply new material of the same or similar grade sufficient to repair or replace the defective material.

LIMITED WATERPROOF WARRANTY

The floor plank is warranted to be waterproof and the structural integrity of the floor plank will not be significantly diminished by exposure to water for the life of the product. While moisture will not affect the floor's integrity, it is probable that, when excessive moisture accumulates in buildings or on building materials, mold (and/or) mildew growth can occur (particularly if the moisture problem remains undiscovered or unaddressed). FORZACORE moisture warranty excludes damage resulting from mold and/or mildew growth due to prolonged exposure to moisture. This warranty is not transferable by the purchaser of the floor.

This Limited Waterproof Warranty excludes all casualty events involving water coming in contact with your floor and failures normally covered by homeowner's insurance including, but not limited to, damages caused by flooding or standing water from leaky pipes, faucets, or household appliances. Also excluded are damages caused by flooding or standing water from **hydrostatic pressure**, other casualty events and/or damage caused by steam cleaning.

The Limited Waterproof Warranty does not cover:

1. Damage to surrounding structure, walls, subfloor, fixtures, furniture, underlayment, moldings, trims, subfloor, heating elements, or anything that is not the floor plank.
2. Damage resulting from mold & mildew growth due to prolonged exposure to moisture.
3. Flooring that is installed outdoors.

WHAT IS NOT COVERED BY THESE WARRANTIES

- This warranty covers material replacement only. Labor will not be considered.
- Damage caused by fire, flooding, or intentional abuse.
- Damage caused by vacuum cleaner beater bar, caster wheels, and cutting from sharp objects. When vacuuming, we recommend using the wand attachment on your vacuum.
- Damage cause by rolling caster wheels (office chairs)
- Heavy furniture must have protection (cups) under the legs to protect the flooring from damage. This type of damage is not warranted.
- Loss of gloss/scratching.
- Dulling or fading of the finish may occur over time, depending on the amount of traffic, ultraviolet (sun light) light, & excessive or improper care and maintenance the floor may receive.

- Minor color, shade, or texture variations between samples or printed color photography and the actual material. Floors that are not graded “regular”.
- Floors that are installed in other than owner-occupied or tenant-occupied residences (Except products that are noted as warranted light commercial).
- Installation-related errors or damage including improper conditioning of job-site and flooring materials. Construction damage after installation.
- Floors damaged by excessive moisture from sources such as flooding and water leakage. Installation defects.
- Damage caused by abuse such as moving appliances across the floor without adequate protection. When moving appliances or heavy furniture, lay a plywood panel on your floor and “walk” the item across it. This protects your floor from scuffing and tears.
- Steam cleaning any vinyl plank floor will void the warranty. The heat produced by the cleaning device may damage the vinyl, causing it to warp, bend, delaminate or dull the finish.

WHAT IS EXCLUDED FROM THESE WARRANTIES?

No retailer, distributor or employee has authority to alter the obligations, limitations, disclaimers or exclusions under any of our warranties. We exclude and will not be liable for or pay incidental, consequential or special damages under our warranties. By this we mean any loss, expense, or damage other than to the flooring itself that may result from a defect in the flooring. Our limited warranties constitute the only express warranties for the product purchased. To the extent permitted by law and for all non-consumer products, all warranties other than our limited warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose, are disclaimed. If any implied warranty arises under state law, any and all implied warranties (including any warranty of merchantability and fitness for a particular purpose) are limited in duration to the duration of this written warranty, to the extent allowed by law.

Some jurisdictions do not allow exclusion or limitations of incidental or consequential damages or limitations on how long an implied warranty lasts, so the above limitations or exclusions may not apply to you.

These warranties give you specific legal rights, and you may also have other rights which vary from jurisdiction to jurisdiction.

INSTALLATION REQUIREMENTS:

- 1- Store planks for 48 hours in the room where they will be installed. Keep room at a minimum of 65°F during that time and during installation.
- 2- All slabs must be tested for moisture prior to installation. New concrete slabs must dry and cured for min. of 60 days. Maximum moisture level per CACI test method is 8 LBS per 1000 sft in 24 hr. Maximum level for ASTM 2170 Relative humidity test method is 85%. Tramex meter concrete moisture level needs to be less than 4%. Any slab over these levels must be addressed, moisture mitigation system should be applied as an added protection and or to regulate moistures levels.
- 3- After installation, the temperature should not fall below 65°F for the first 48 hours, and not below 55°F after that.
- 4- The subfloor must be level (3/16” in a Ten (10) foot radius), clean, and free of wax, grease, oil or dust.
- 5- Radiant heat should not exceed a temperature of 85 degrees

If necessary, patch or fill any cracks in the subfloor with patch, or latex underlayment. Use embossing leveler to smooth any texture or embossing on the old floor. Install over smooth, well-bonded resilient floors or over dry concrete and wood floors with a plywood overlay.

This limited product warranty does not cover any product installed with visible defects. Installation errors are the responsibility of the installer. While installations not performed according to our requirements do not void the product warranty, damage or problems with the flooring related to improper installation are not covered.

WARRANTY OWNER

This warranty applies only to Professionally Installed installations. This warranty extends only to the original end user and is not transferable.

PLEASE KEEP YOUR RECEIPT OR OBTAIN IT FROM THE ORIGINAL PURCHASER.

FORZACORE will require the flooring receipt in order to verify date and proof of purchase to resolve any problems that may occur. For professionally installed floors, the original receipt for installation labor may also be required.



ELITE SERIES

20 MIL 2.5MM GLUE DOWN VINYL WARRANTY

PRO 20 COLLECTION

15 YEAR RESIDENTIAL WARRANTY FOR DRYBACK FLOORING

Will not wear through.

Will be free of manufacturing defects.

Will not rip or tear from normal household use. (If Properly Protected)

Will not permanently indent from normal household use. (If properly Protected)

Will not discolor from the bottom-up from the underlayment panels, as well as mold, mildew or alkali.

Wear through is defined as loss of the floor design due to normal household use. We recommend using floor protectors. As a general rule of thumb, the heavier the item, the wider the floor protectors should be.

COMMERCIAL INSTALLATIONS 10 YEAR LIMITED WARRANTY

For commercial installations (example: common areas in multi-unit dwellings and low traffic retail shops) the product is warranted to be free from manufacturing defects for 10 years from the date of purchase. If a defect covered by this warranty is reported in writing to FORZACORE within 90 days of purchase, FORZACORE will supply new material of the same or similar grade sufficient to repair or replace the defective material.

LIMITED WATERPROOF WARRANTY

The floor plank is warranted to be waterproof and the structural integrity of the floor plank will not be significantly diminished by exposure to water for the life of the product. While moisture will not affect the floor's integrity, it is probable that, when excessive moisture accumulates in buildings or on building materials, mold (and/or) mildew growth can occur (particularly if the moisture problem remains undiscovered or unaddressed). FORZACORE moisture warranty excludes damage resulting from mold and/or mildew growth due to prolonged exposure to moisture. This warranty is not transferable by the purchaser of the floor.

This Limited Waterproof Warranty excludes all casualty events involving water coming in contact with your floor and failures normally covered by homeowner's insurance including, but not limited to, damages caused by flooding or standing water from leaky pipes, faucets, or household appliances. Also excluded are damages caused by flooding or standing water from **hydrostatic pressure**, other casualty events and/or damage caused by steam cleaning.

The Limited Waterproof Warranty does not cover:

1. Damage to surrounding structure, walls, subfloor, fixtures, furniture, underlayment, moldings, trims, subfloor, heating elements, or anything that is not the floor plank.
2. Damage resulting from mold & mildew growth due to prolonged exposure to moisture.
3. Flooring that is installed outdoors.

WHAT IS NOT COVERED BY THESE WARRANTIES

- This warranty covers material replacement only. Labor will not be considered.
- Damage caused by fire, flooding, or intentional abuse.
- Damage caused by vacuum cleaner beater bar, caster wheels, and cutting from sharp objects. When vacuuming, we recommend using the wand attachment on your vacuum.
- Damage cause by rolling caster wheels (office chairs)
- Heavy furniture must have protection (cups) under the legs to protect the flooring from damage. This type of damage is not warranted.
- Loss of gloss/scratching.
- Dulling or fading of the finish may occur over time, depending on the amount of traffic, ultraviolet (sun light) light, & excessive or improper care and maintenance the floor may receive.

- Minor color, shade, or texture variations between samples or printed color photography and the actual material. Floors that are not graded “regular”.
- Floors that are installed in other than owner-occupied or tenant-occupied residences (Except products that are noted as warranted light commercial).
- Installation-related errors or damage including improper conditioning of job-site and flooring materials. Construction damage after installation.
- Floors damaged by excessive moisture from sources such as flooding and water leakage. Installation defects.
- Damage caused by abuse such as moving appliances across the floor without adequate protection. When moving appliances or heavy furniture, lay a plywood panel on your floor and “walk” the item across it. This protects your floor from scuffing and tears.
- Steam cleaning any vinyl plank floor will void the warranty. The heat produced by the cleaning device may damage the vinyl, causing it to warp, bend, delaminate or dull the finish.

WHAT IS EXCLUDED FROM THESE WARRANTIES?

No retailer, distributor or employee has authority to alter the obligations, limitations, disclaimers or exclusions under any of our warranties. We exclude and will not be liable for or pay incidental, consequential or special damages under our warranties. By this we mean any loss, expense, or damage other than to the flooring itself that may result from a defect in the flooring. Our limited warranties constitute the only express warranties for the product purchased. To the extent permitted by law and for all non-consumer products, all warranties other than our limited warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose, are disclaimed. If any implied warranty arises under state law, any and all implied warranties (including any warranty of merchantability and fitness for a particular purpose) are limited in duration to the duration of this written warranty, to the extent allowed by law.

Some jurisdictions do not allow exclusion or limitations of incidental or consequential damages or limitations on how long an implied warranty lasts, so the above limitations or exclusions may not apply to you.

These warranties give you specific legal rights, and you may also have other rights which vary from jurisdiction to jurisdiction.

INSTALLATION REQUIREMENTS:

- 1- Store planks for 48 hours in the room where they will be installed. Keep room at a minimum of 65°F during that time and during installation.
- 2- All slabs must be tested for moisture prior to installation. New concrete slabs must dry and cured for min. of 60 days. Maximum moisture level per CACI test method is 8 LBS per 1000 sft in 24 hr. Maximum level for ASTM 2170 Relative humidity test method is 85%. Tramex meter concrete moisture level needs to be less than 4%. Any slab over these levels must be addressed, moisture mitigation system should be applied as an added protection and or to regulate moistures levels.
- 3- After installation, the temperature should not fall below 65°F for the first 48 hours, and not below 55°F after that.
- 4- The subfloor must be level (3/16” in a Ten (10) foot radius), clean, and free of wax, grease, oil or dust.
- 5- Radiant heat should not exceed a temperature of 85 degrees

If necessary, patch or fill any cracks in the subfloor with patch, or latex underlayment. Use embossing leveler to smooth any texture or embossing on the old floor. Install over smooth, well-bonded resilient floors or over dry concrete and wood floors with a plywood overlay.

This limited product warranty does not cover any product installed with visible defects. Installation errors are the responsibility of the installer. While installations not performed according to our requirements do not void the product warranty, damage or problems with the flooring related to improper installation are not covered.

WARRANTY OWNER

This warranty applies only to Professionally Installed installations. This warranty extends only to the original end user and is not transferable.

PLEASE KEEP YOUR RECEIPT OR OBTAIN IT FROM THE ORIGINAL PURCHASER.

FORZACORE will require the flooring receipt in order to verify date and proof of purchase to resolve any problems that may occur. For professionally installed floors, the original receipt for installation labor may also be required.

Style	Wood
Construction	Luxury Vinyl Tile Non-ortho Phthalate
Classification	ASTM F1700 Class III, Type B
Total Thickness	0.098" (2.5 mm)
Wear Layer Thickness	20 mil (0.55 mm)
Wear Layer	Urethane
Edge Treatment	Micro-bevel
Sizes	7.25" x 48" (184 x 1219 mm)
Colors	10
Packaging	48.29 ^{qt} 43 lbs
Adhesive	Porous & Non-porous Substrates: Full Spread, Transitional Pressure Sensitive

Installation Method All arrows in the same direction. Planks should have end joints offset by at least 6" and staggered to create a random appearance.

Testing	
HUD/FHA	Passes
Flexibility (ASTM F137)	Passes - 1" Mandrel - No Crack/Break
Dimensional Stability (ASTM F2199)	Passes - Max 0.020 in/in ft
Squareness (ASTM F2055)	Passes - Max 0.010"
Static Load (ASTM F970 mod.)	Passes - 2,000 PSI; Residual Indent $\leq 0.005"$
Residual Indentation (ASTM F1914)	Passes - $< 8\%$ Avg / 10% Single Value
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²
Smoke Density (ASTM E662)	Passes - ≤ 450
Slip Resistance (ASTM C1028)	Passes - ≥ 0.5 Leather; 0.6 Rubber
Resistance to Light (ASTM F1515)	Passes
Chemical Resistance (ASTM F925)	Passes
Resistance to Heat (ASTM F1514)	Passes

Environmental Data	
Rapidly Renewable Content	Contains 2% rapidly renewable resource content
Indoor Air Quality	FloorScore Certified; CDPH v1.2-2017
Product Declarations	Third Party Verified EPD, HPD
Carbon Offset	105% Cradle to Gate (A1 - A3), visit website for more information
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials

Warranty	
	Limited 10-Year Commercial Warranty Limited 15-Year Residential